

KNX MANUFACTURER

Made in Belgium

elausys.be

ELECTRONIC & AUTOMATION SYSTEMS



ABOUT US

We design and manufacture innovative products for home and building automation based on the worldwide standard KNX.

ELAUSYS is a certified KNX manufacturer of the KNX Association

- Innovative product range
- Made in Belgium
- ISO9001 assembly
- Customized and OEM product development
- Engineering services



From binary inputs to DIN rails actuators, our product range covers all needs for a modular and cost effective automation system.

System • KNX Power Supply 640mA • KNX gateway for Jablotron alarm systems Gateways • KNX gateway for Paradox alarm systems • KNX gateway for GE Interlogix NX alarm systems KNX Master actuator 8 x 10A Actuators Extension modules 2, 4 or 8 x 10A • Extension modules 2, 4 or 8 x 16A • KNX Input gateway for up to 60 input devices Inputs • Binary input 1, 2, 4, 6, 8-fold + dual temperature

Coming soon



KNX Power Supply 640 mA



- KNX POWER SUPPLY 640mA
- Integrated KNX choke
- 230VAC, 50/60Hz input, protected by 1A T replaceable fuse
- KNX line output
- Auxiliary 30VDC output
- Total output current limitation approx. 1.2A
- Output overvoltage protection
- Reset circuit, Set / Reset button on front panel
- LED indicators for *voltage OK, Current limitation, Short-Circuit, Reset*
- 3-Stage KNX overvoltage protection

The KNX POWER SUPPLY 640mA is a DIN Rail mounted KNX device with integrated choke, to directly power a KNX line. An auxiliary 30V output is available for some extra loads, as displays, binary inputs or the Elausys *Master Actuator,...*



Jablotron KNX Interface



- KNX Interface for Jablotron 100 alarm systems
- Real time status of up to 96 zones
- Up to 32 bidirectional input/output (PG)
- Control of up to 4 areas (arm/partial/disarm)
- 9 status per area (intrusion, entry, exit, fire,...)
- Recall of KNX scenes for each status
- Power supply from the KNX bus
- Integrated 12VDC output power supply (for JA-121T)
- Built-in termination resistor for RS485
- Communication fault monitoring

A bidirectional KNX interface for the popular Jablotron alarm system.

It allows integrators to take advantage of a fully integrated alarm system including KNX scenarios, automatic lighting using the motion detectors, arming or monitoring the system using a KNX visualization.



PARADOX KNX Interface

ELAUSYS EVO-KNX is a KNX gateway for the Paradox EVO alarm systems.




- KNX Interface for Paradow EVO alarm systems
- Up to **30 PGM status**
- Up to **96 zones status**
- Control up to 16 virtual inputs
- Control up to 4 areas (arm/partial/disarm)
- 9 status per area (alarm, entry, exit, fire,...)
- Recall of KNX scenes for each status
- Galvanic insulation from the KNX bus

A bidirectional KNX interface for the popular Paradox alarm system.

It allows integrators to take advantage of a fully integrated alarm system including KNX scenarios, automatic lighting using the motion detectors, arming or monitoring the system using a KNX visualization.



GE NetworX KNX Interface



- KNX Interface for GE Interlogix NetworX alarm systems
- Up to **96 zones status**
- Control up to 4 areas (arm/partial/disarm)
- 9 status per area (alarm, entry, exit, fire,...)
- Recall of KNX scenes for each status
- Galvanic insulation from the KNX bus

A bidirectional KNX interface for the popular NetworX alarm system.

It allows integrators to take advantage of a fully integrated alarm system including KNX scenarios, automatic lighting using the motion detectors, arming or monitoring the system using a KNX visualization.



Modular KNX Actuators



- Modular and extensible actuator system
- Up to **72 channels** with 8 extensions modules
- Extension modules for 2, 4 or 8 channel in 10 or 16A
- Switch, staircase, shutter or blind function for any channel
- Number of channels fit exactly to your needs
- Cost Effective, price for each channel becomes very attractive
- Reduced space by using compact modules

A modular actuator system with extension modules to fit all your applications, from small to large installation with only one KNX master device!



KNX Input Gateway



- Up to **60 Binary Inputs**
- Up to **30 Sensors**
- Each device has a built-in temperature sensor
- Extra low power
- Fully compatible with all standard KNX functions
- Configuration with ETS
- Use a **single KNX cable** for all your devices
- Elausys devices are interchangeable with KNX devices at any time
- Cost Effective, price for each input becomes very attractive

A gateway for connecting binary inputs and sensors to KNX. A cost effective and powerful solution. Fully compatible with KNX, all your inputs are managed from a single KNX device!



Input Devices



- 1 to 8 **Binary input** for push buttons or switches
- 1 built-in temperature sensor ranging from -5 to 45°C
- 1 input for an external temperature probe
- Individual configuration for short and long presses
- Configuration on the KNX Input gateway using ETS
- Fully compatible with all KNX Functions
- Optional housing when required
- Cost effective solution for push buttons and switches

Binary inputs modules are easy to fit behind pushbuttons, ranging from 1 to 8 binary inputs, each device include an internal temperature sensor and an extra input for an external temperature probe.



CONTACT US FOR MORE INFORMATION

Elausys SPRL
Rue camille Hubert 7-9
5032 Les Isnes (Gembloux)
Belgium

Tel: +32(0)81/98.06.52 Mobile: +32(0)487.244.507 Email: info@elausys.be

Web: elausys.be